

WHAT IS CLAIMED IS:

Sub 1027
 5 1. A drive mechanism for a bicycle transmission assist mechanism comprising:
 a crank arm having a rotational axis; and
 a drive member including:

a first abutment facing a forward rotational direction of the crank arm; and
 a non-concave first sloped surface extending from a radially outer portion of
~~the abutment and facing a rearward rotational direction of the crank arm.~~

10 2. The drive mechanism according to claim 1 wherein the first abutment is
 substantially perpendicular to an outer peripheral surface of the crank arm.

15 3. The drive mechanism according to claim 1 wherein the first sloped surface has an
 arcuate shape.

✓ 4. The drive mechanism according to claim 1 wherein the drive member is coaxial
 with the rotational axis.

20 5. The drive mechanism according to claim 1 wherein the drive member is one-piece
 with the crank arm.

✓ 6. The drive mechanism according to claim 1 wherein the drive member comprises an
 annular drive ring mounted around the rotational axis.

Sub 25
~~7. The drive mechanism according to claim 6 wherein an inner peripheral surface of
 the drive ring includes a plurality of drive ring splines, and wherein an outer peripheral
 surface of the crank arm includes a plurality of crank arm splines that engage the plurality of
 drive ring splines.~~

30 Sub 25
 8. The drive mechanism according to claim 1 wherein the drive member includes:
 a second abutment facing the forward rotational direction of the crank arm; and
 a non-concave second sloped surface facing the rearward rotational direction of the

crank arm.

9. The drive mechanism according to claim 8 wherein the first abutment is located substantially 180° from the second abutment.

5

10. The drive mechanism according to claim 9 wherein the drive member is coaxial with the rotational axis.

11. The drive mechanism according to claim 10 wherein the drive member is one-

10 piece with the crank arm.

12. The drive mechanism according to claim 11 wherein the first abutment is substantially perpendicular to an outer peripheral surface of the crank arm, and wherein the second abutment is substantially perpendicular to an outer peripheral surface of the crank arm.

15

13. The drive mechanism according to claim 12 wherein the first sloped surface has an arcuate shape, and wherein the second sloped surface has an arcuate shape.

20

14. The drive mechanism according to claim 10 wherein the drive member comprises an annular drive ring mounted around the rotational axis.

15. The drive mechanism according to claim 14 wherein the first abutment is substantially perpendicular to an outer peripheral surface of the crank arm, and wherein the second abutment is substantially perpendicular to an outer peripheral surface of the crank arm.

25

16. The drive mechanism according to claim 15 wherein the first sloped surface has an arcuate shape, and wherein the second sloped surface has an arcuate shape.

30

17. The drive mechanism according to claim 16 wherein an inner peripheral surface of the drive ring includes a plurality of drive ring splines, and wherein an outer peripheral

surface of the crank arm includes a plurality of crank arm splines that engage the plurality of drive ring splines.

18. The drive mechanism according to claim 1 wherein the crank arm is a left-side crank arm.

19. The drive mechanism according to claim 1 wherein the crank arm is a right-side crank arm.

20. The drive mechanism according to claim 1 wherein the rotational axis is disposed at a first end of the crank arm, and further comprising a pedal mounting hole disposed at an opposite second end of the crank arm.

21. The drive mechanism according to claim 1 wherein the crank arm includes a sprocket mounting member for mounting a sprocket to the crank arm.

22. The drive mechanism according to claim 21 wherein the sprocket mounting member comprises four sprocket mounting arms.

23. The drive mechanism according to claim 21 further comprising:
a large diameter sprocket retained to the sprocket mounting member; and
a small diameter sprocket retained to the sprocket mounting member.

24. The drive mechanism according to claim 23 wherein the large diameter sprocket includes a shift assist mechanism for assisting travel of a chain between the small diameter sprocket and the large diameter sprocket.

25. The drive mechanism according to claim 24 wherein the shift assist mechanism comprises a chain support member disposed on a side surface of the large diameter sprocket facing the small diameter sprocket.

26. The drive mechanism according to claim 23 wherein a first plane containing an

inner side surface of the drive member is disposed laterally inwardly from an inner side surface of the small diameter sprocket.

27. The drive mechanism according to claim 26 wherein a second plane containing an outer side surface of the drive member is disposed laterally inwardly from the inner side surface of the small diameter sprocket.

28. The drive mechanism according to claim 1 further comprising a dust seal disposed along a circumferential surface of the crank arm.

29. The drive mechanism according to claim 1 wherein an inner side surface of the crank arm includes a groove.

30. The drive mechanism according to claim 29 wherein the groove is an annular groove.

31. The drive mechanism according to claim 1 wherein the crank arm has a crank axle mounting hole, and further comprising a plurality of splines disposed in the crank axle mounting hole.

32. The drive mechanism according to claim 1 wherein an outer peripheral surface of the drive member at a location of intersection with a radially inner portion of the first abutment extends at a substantially constant radius of curvature for more than 20°.

33. The drive mechanism according to claim 1 wherein the crank arm has a crank axle mounting hole and a plurality of splines disposed in the crank axle mounting hole, and wherein a plane containing an inner side surface of the drive member is disposed laterally inwardly from laterally inner ends of the plurality of splines.

34. The drive mechanism according to claim 33 wherein the plane is disposed at least 5 millimeters laterally inwardly from the laterally inner ends of the plurality of splines.

Sub
A7

35. A drive mechanism for a bicycle transmission assist mechanism comprising:
a bicycle crank arm having a crank axle mounting boss; and
only two abutments disposed on an outer surface of the crank axle mounting boss and
facing a forward rotational direction of the crank arm.

5

36. A drive mechanism for a bicycle transmission assist mechanism comprising:
a bicycle crank arm having a crank axle mounting boss; and
a drive member disposed at the crank axle mounting boss and including:

an outer peripheral surface;

10

wherein an abutment is disposed on the outer peripheral surface and facing a
forward rotational direction of the crank arm; and

wherein the outer peripheral surface at a location of intersection with a radially
inner portion of the abutment extends convex for at least 20° .

15

37. A drive mechanism for a bicycle transmission assist mechanism comprising:
a crank arm extending along a crank arm axis and having a crank axle mounting boss
defining a crank axle mounting hole; and

20

a drive member disposed at the crank axle mounting boss and radially outwardly from
the crank axle mounting hole, wherein the drive member forms an abutment disposed at an
inner side of the crank arm, facing in a forward rotational direction and spaced laterally from
an inner side surface of the crank arm.

Add
A7
Add
C6